



Weatherwell

ALUMINIUM MAINTENANCE PROGRAM

The Weatherwell Aluminium Shutter Collection is perfectly situated to bringing indoor and outdoor spaces closer together. Strong, durable and secure, Weatherwell shutters are specifically designed to weather the elements.

As a rule, stainless steel hardware and fittings are used to resist rust and corrosion, particularly in coastal atmospheres and applications. However, as for all quality products, cleanliness is essential for maximum resistance to corrosion.

CLEANING WEATHERWELL ALUMINIUM SHUTTERS

Wipe over the shutters using a nonabrasive cloth or sponge with warm soapy water. A garden hose can be used applying the same principles.

Concentrate on the areas where the stainless steel hardware is attached to the shutter.

Remove any salt residue, tannin stains caused by trees and any other marks created.

On completion of the cleaning process, spray a light film of silicone lubricant to any operational hardware such as the tracking system. Ensure these areas are fully dry prior to this application.

We recommend cleaning your aluminium shutters on a routine basis every six months.

For shutters installed in premises close to coastal or saltwater environments the following cleaning timeframes are recommended.

COASTAL AREA RECOMMENDATIONS

PROXIMITY	CLEANING TIME FRAME
Direct beach front	Weekly
1 km radius	Monthly
10km radius	Quarterly

OVERVIEW

By following these simple cleaning guidelines, possible corrosion of components can be avoided and the beauty, flexibility and durability of Weatherwell shutters can be fully enjoyed and appreciated.